

## High Performance Multi-Port Reader

### Applications

- Parking Management
- Vehicle Access Control
- Asset Tracking
- Conveyor Application
- Factory Automation Control
- Item Tracking Management



Regor™

### Product Description

Regor multi-port reader is powerful and easy to use and has great value for money.

Regor is perfect for use in Production Process Management, Track and Trace and Vehicle Secure Access Control applications.

The reader has 4 fast-switching and configurable mono-static antenna ports and support Ethernet and serial interfaces for fast and flexible communication with host.

*Your Success is Our Vision*





## Specifications

Dimensions	36 x 126 x 35 mm ( 5.36 x 4.96 x 1.38" )
Weight	630g ( 1.39lbs )
Protocol	ISO18000-6C/63 EPC C1G2
Communication	Ethernet (RJ45), Serial (RS-232)
GPIO	2 IN, 3 OUT
Frequency Range	860 - 960 MHz (adjustable)
RF Output Power	10 - 30 dBm, 1 dBm steps
Operating Temperature	-20°C~ +70°C (-4°F to +158°F)
Storage Temperature	-20°C~ +50°C (-4°F to +122°F)
Ingress Protection Power Supply	+9.0 VDC
Compliance	FCC, ETSI, CE, NCC, KCC, TELEC
API	C#, C++, Raw Protocol