




Windshield Transponder

Applications

- Electronic Toll Collection
- Electronic Vehicle Registration
- Parking and Access Control
- Vehicle Emissions Inspection
- Fleet Management
- Proof of Insurance



Vektra™

Product Description

With its new ultra-tuned design and patented physical security features, Vektra Windshield Transponder delivers extremely high read and write performance in Vehicle Applications. Vektra is designed and tuned specifically for glass windshield of a vehicle and is especially effective for High Speed / Open Road Tolling Systems.

Designed as a vehicle transponder from the ground up, Vektra is constructed to provide reliable reading for years, even in extreme weather conditions. Vektra's transponder antenna is ultra-tuned to provide high reliability and security in vehicle applications such as Tolling, Electronic Vehicle Registration and Secure Access Systems.

Vektra utilizes a flexible memory architecture which provides an optimum allocation of memory and interoperability. It is ideal to be used in high security applications. Vektra's User memory can be secured by the chip's read-lock and/or write-lock features allowing the transponder to support a variety of public/private usage models. The chip also features a factory pre-programmed and permanently locked 64-bit serial number that cannot be altered. This serial number in conjunction with the EPC data bank can be used to generate a Unique Access Code for each and every transponder.

Your Success is Our Vision





Standard Features

- Specially Designed for Vehicle Applications
- Improved High Read Rate Performance
- Tamper Evident Feature
(Non-Removable, Non-Transferable)
- IR/UV Light Protection
- Standard 1 Year Warranty

Additional Options

- Patented BOR (Break on Removal)
- Custom Color Press or Variable Printing
- Custom Chip Encoding
- Transparent/White Label
- 1-part Label
- 2-part Label

Specifications

Dimensions	1-part Label : 100 x 30mm (3.94 x 1.18") 2-part Label : 100 x 40mm (3.94 x 1.57")
RF Protocol	ISO 18000-6C/63 EPC C1G2
Operating Frequency	860 - 960 MHz
Operating Temperature (Installed)	-50°C to +85°C (-58°F to +185°F)
Relative Humidity (RH) (Installed)	100% Condensing Humidity
Chip Type	Alien H3 chip
EPC	96 - 480 Bits
On-Chip Memory	800 Bits
Unique TID	64 Bits
Access Password	32 Bits
Kill Password	32 Bits
EEPROM Data Retention	50 Years
EEPROM Write Endurance	100,000 Cycles
Custom TID Bitmask	Optional
Password Authentication	Yes