

High Performance Multi-Port Reader

Applications

- Parking Management
- Vehicle Access Control
- Asset Tracking
- Conveyor Application
- Factory Automation Control
- Item Tracking Management



Regor™

Product Description

Regor multi-port reader is powerful and easy to use and has great value for money.

Regor is perfect for use in Production Process Management, Track and Trace and Vehicle Secure Access Control applications.

The reader has 4 fast-switching and configurable mono-static antenna ports and support Ethernet and serial interfaces for fast and flexible communication with host.

Your Success is Our Vision



Specifications

| | |
|---------------------------------|--|
| Dimensions | 36 x 126 x 35 mm (5.36 x 4.96 x 1.38") |
| Weight | 630g (1.39lbs) |
| Protocol | ISO18000-6C/63 EPC C1G2 |
| Communication | Ethernet (RJ45), Serial (RS-232) |
| GPIO | 2 IN, 3 OUT |
| Frequency Range | 860 - 960 MHz (adjustable) |
| RF Output Power | 10 - 30 dBm, 1 dBm steps |
| Operating Temperature | -20°C~ +70°C (-4°F to +158°F) |
| Storage Temperature | -20°C~ +50°C (-4°F to +122°F) |
| Ingress Protection Power Supply | +9.0 VDC |
| Compliance | FCC, ETSI, CE, NCC, KCC, TELEC |
| API | C#, C++, Raw Protocol |